POSIFLEX™

Be the Pioneer, Be the Leader

KEY FEATURES

- VIA NANO™ 1.6 GHz w/ 1M L2 Cache
- Die-Cast Aluminum Alloy Housing for maximum heat diffusion
- Operates in a wide range of environments and temperatures. 14°F ~ 122°F (-10°C ~ 50°C)
- Available configurations w/ 2GB or 4GB DDR3
- Precisely designed, with strict revision control to maximize the system's lifecycle
- Stringent third party HALT / HASS tested for extensive temperature cycling, vibration, drop, shock, static electricity and emission tolerance

KS6700 Series

The Enhanced Price Performer

The KS6715 now takes over where the KS6215 left off. Everything you loved about its predecessor, you will love even more in the KS6715 with its increased performance, ports, memory, and complete peripheral compatibility. It is a price-performer, giving you more for your hardware investment.

Featuring our patented aluminum chassis for maximum heat diffusion, a 1.6GHz CPU, it offers 110% more performance over its predecessor with its increased functionality. Providing even greater energy efficiency, look to the KS6715 for additional costs savings.

Available in a desktop configuration, which easily converts to a wall mount solution, it offers you adaptability and scalability to propel your business to greater heights.

Call today and find out how the KS6715 can boost your sales and help you grow your bottom line.

For more information call 888-968-1668 today!

About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of innovative excellence with more than 30 patents for innovation

Global presence

Two ISO 9001/9002/14001 Certified Facilities

See the King Pin in POS Reliability!

© 2012 Posiflex and the Posiflex logo is a trademark of Posiflex Business Machines, Inc.
All other brand and company names are the property of their respective owners.

Specifications

SPECIFICATIONS	KS6715
Processor	VIA NANO™ 1.6 GHz w/ 1M L2 Cache
System Memory	DDR3 1066MHz SO-DIMM x1 Slot, (2GB Default)
Memory Configurations	2GB or 4GB
Power Supply	12V DC power adaptor, 60W
Storage Device	2.5” SATA 160GB HDD or SSD Kit (Optional)
Supported OS	POSREADY 7/Win XP Pro/Win 7 Pro/Linux[1]
DISPLAY	
LCD	15” TFT LCD, 1024x768 (XGA)
Touch Function	5-Wire Resistive, USB Interface
Brightness Control	Digital Push button
Tilt Adjustment	From 15° to 70°
PHYSICAL DIMENSIONS	
Dimensions (WxDxH)	Base Mount: 14.9" x 11.5" x 14.2"; Wall Mount: 14.9" x 2.71" x 12"
Weight (Pounds)	Base Mount: 16 lbs; Wall Mount: 11 lbs
CONNECTIVITY	
LAN Port	1x RJ-45 10/100/1000 Base T-Ethernet
Serial Port	4x 9-pin male d-sub (5V/12V support on COM1/COM2/COM3/COM4)
VGA Port	1x 15-pin female d-sub RGB analog (12V support for Posiflex LCD Monitors)
CR Port	1x RJ-11 port controls 2 cash drawers (max)
Standard USB Port(s)	6x USB 2.0 Type A port, (4x on I/O panel, 2x in side cover)
Parallel Port	Optional (P/N: 21862033420)



AVAILABLE SERVICES

- **Standard and Extended Warranty**
  Extend your depot warranty up to 5 years.
- **Advance Exchange**
  We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- **OnSite Service**
  Expert technicians will efficiently handle the complete equipment swap and return process.
- **Regional Repair Depots**
  Three regional depots assure fast turn-around time on repairs.
- **Post Warranty Support**
  Spare parts, in addition to a flat rate repair program, for post warranty needs.
- **Installation Services**
  Let our nationwide network of experts stage and install your equipment.
- **OEM Design and Integration**
  Our Product Development Team helps design equipment, for custom hardware applications.

PERIPHERALS

Magnetic Stripe Reader - SD402
Biometric or Encrypted options

Rear Mount Display - PD2604
2 x 20 Character VFD*

Thermal Printer - PP8000
80mm Wide, Printing Speed: 220mm/second

Cash Drawer - CR6300
Printer Driven and USB options available

*Vacuum Fluorescent Display
[1]Driver Support Only

See www.PosiflexUSA.com for a complete line of peripherals

POSIFLEX™
Be the Pioneer, Be the Leader
30689 Huntwood Avenue
Hayward, CA 94544
Toll-free: 888.968.1668
Phone: 510.429.7097
Fax: 510.475.0982
E-mail: sales@posiflexusa.com
www.posiflexusa.com

Windows® Embedded Partner
intel inside
RoHS
Green POS Green Earth

Rev. 03/30/12