

A-4212, A-4310, A-4408, & A-4606**Please refer to your supplier for Printer Model pricing****Printer Model**

Right Hand, A-4212E 8MB FLASH	A2
Right Hand, A-4310E 8MB FLASH	A3
Right Hand, A-4408E 8MB FLASH	A4
Right Hand, A-4606E 8MB FLASH	A6
Left Hand, A-4212E 8MB FLASH	B2
Left Hand, A-4310E 8MB FLASH	B3
Left Hand, A-4408E 8MB FLASH	B4
Left Hand, A-4606E 8MB FLASH	B6

Custom Kit

Datamax Standard Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used

Do not Include this Option	0
----------------------------	---

Cutter / Ribbon Saver / Top Pinch Roller Option

Do Not Include This Option	0
Cutter Option (RH models only)	4
Top Pinch Roller Option	5
Ribbon Saver and Top Pinch Roller Option	C
Top Pinch Roller and Cutter Option (RH models only)	D
Ribbon Saver, Top Pinch Roller, and Cutter Option (RH models only)	E

Font Expansion Option

Do Not Include This Option	0
Kanji Gothic B	H
Simplified Chinese	N
Korean Hangul Font	V
PL-Z Emulation	1
PL-I Emulation	2

Interface Options

Do Not Include This Option	0
DMXrfNet III Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
DMXrfNet III Wireless B/G Option	S

Not Used

Do Not Include This Option	0
----------------------------	---

Misc. Options

Do Not Include This Option	0
Remote Display Option	F
Remote Display "Ready" Option	G
Cover Open Sensor	V

Remote Display Option & Cover Open Sensor	X
Remote Display "Ready" Option & Cover Open Sensor	Z

A-6212 & A-6310

Please refer to your supplier for Printer Model pricing

Printer Model

Right Hand, A-6212E 8MB FLASH	C2
Right Hand, A-6310E 8MB FLASH	C3
Left Hand, A-6212E 8MB FLASH	D2
Left Hand, A-6310E 8MB FLASH	D3

Custom Kit

Datamax Standard Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used

Do not Include this Option	0
----------------------------	---

Ribbon Saver / Top Pinch Roller Option

Do Not Include This Option	0
Top Pinch Roller Option	5
Ribbon Saver and Top Pinch Roller Option	C

Font Expansion Option

Do Not Include This Option	0
Kanji Gothic B	H
Simplified Chinese	N
Korean Hangul Font	V
PL-Z Emulation	1
PL-I Emulation	2

Interface Options

Do Not Include This Option	0
DMXrfNet III Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
DMXrfNet III Wireless B/G Option	S

Not Used

Do Not Include This Option	0
----------------------------	---

Misc. Options

Do Not Include This Option	0
Remote Display Option	F
Remote Display "Ready" Option	G
Cover Open Sensor	V
Remote Display Option & Cover Open Sensor	X
Remote Display "Ready" Option & Cover Open Sensor	Z

E-Class Mark III

E	-	-								
Printer Model										
Basic Desktop Barcode Printer: E-4204B, 203dpi, 4ips, LED/Button UI										B2
Basic Desktop Barcode Printer: E-4304B, 300dpi, 4ips, LED/Button UI										B3
Advanced Desktop Barcode Printer: E-4205A, 203dpi, 5ips, Adjustable Sensor, LED/Button UI										A2
Advanced Desktop Barcode Printer: E-4305A, 300dpi, 5ips, Adjustable Sensor, LED/Button UI										A3
Professional Desktop Barcode Printer: E-4206P, 203dpi, 6ips, Adjustable Sensor, LCD/Navigation Buttons UI										P2
Professional Desktop Barcode Printer: E-4305P, 300dpi, 5ips, Adjustable Sensor, LCD/Navigation Buttons UI										P3
Professional+ Desktop Barcode Printer: E-4206L, 203dpi, 6ips, Adjustable Sensor, LCD/Navigation Buttons UI, Large Case										L2
Professional+ Desktop Barcode Printer: E-4305L, 300dpi, 5ips, Adjustable Sensor, LCD/Navigation Buttons UI, Large Case										L3
Product Kit										
Standard Kit - Includes: Packaging, Quick Start Guide, CD, Warranty Card										00
No Kit - Includes: No additional contents										01
China Kit										07
Printing Technology										
Direct Thermal										0
Thermal Transfer and Direct Thermal										1
A/C Power Supply and International Cord										
No Power Supply or Cord										0
Autoranging Power Supply With South Africa Cord										B
Autoranging Power Supply With British & European Power Cords										E
Autoranging Power Supply With Israel Power Cord										G
Autoranging Power Supply Without Power Cord										H
Autoranging Power Supply With US Power Cord										J
Autoranging Power Supply With British Power Cord										K
Autoranging Power Supply With European Power Cord										L
Autoranging Power Supply With Swiss Power Cord										M
Autoranging Power Supply With Chinese Power Cord										S
Autoranging Power Supply With Australian Power Cord										T
Autoranging Power Supply With Italian Power Cord										V
Autoranging Power Supply With Argentinian Power Cord										W
Autoranging Power Supply With Japanese Power Cord										Z
Autoranging Power Supply With Straight Brazil Power Cord										5
Exit Options										
Tear Edge										0
Peeler w/Label Sensor										P
Cutter w/Label Sensor (Advanced and Professional Models Only)										G
ILPC Font Option										
Standard Font Set (<i>see spec sheet</i>)										0
ILPC - CG Times Font Family - unlock										A
Kanji Gothic B Font										K
Simplified Chinese Font										N
Korean Hangul Font										V
Command Language Compatibility										
DPL; Standard (<i>Pro &Pro+ Models Only</i>)										0
Auto - DPL, PL-Z(ebra), PL-E(ltron) Emulation (<i>Pro &Pro+ Models Only</i>)										1
PL-I - Intermec Emulation (<i>Pro &Pro+ Models Only</i>)										2
PL-B - Boca/FGL Emulation (<i>Pro &Pro+ Models Only</i>)										3
Netira - Auto (<i>Basic & Advanced Models Only</i>)										5
Interface Options										
Serial, USB (Basic Model Only)										B
Serial, Parallel, USB & LAN (Advanced Models Only)										A
Serial, Parallel, USB, LAN, USB Host, RTC (Pro Models Only)										P
Serial, Parallel, USB, LAN, USB Host, RTC & 802.11 Wireless A/B/G (Pro Models Only)										Q
Serial, Parallel, USB, LAN, USB Host, RTC & Bluetooth (Pro Models Only)										V

Power Case	
Not Used	0
MPU-4000 Mobile Power Unit (battery pack): Power supply option is assembled into the unit. Only attaches to Basic, Advanced and Pro model.	4
Misc. Options	
No Option (<i>standard</i>)	0
Media Guide Chute (for loading external media; not compatible with Pro+ model)	1
Cabinet Lock and Tethering Slot (Pro+ only)	L

H-4212, H-4310, H-4408, & H-4606

C		-		-	4							
---	--	---	--	---	---	--	--	--	--	--	--	--

Printer Model

H-4212 - 4"-203 DPI, 12 IPS, Thermal Transfer Printer	42
H-4310 - 4"-300 DPI, 10 IPS, Thermal Transfer Printer	43
H-4408 - 4"-400 DPI, 8 IPS, Thermal Transfer Printer	34
H-4606 - 4"-600 DPI, 6 IPS, Thermal Transfer Printer	36

Custom Kit

Datamax Standard Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Cast Peel & Present Option and Internal Rewind	9
Basic Peel & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Applicator Card Kit	P
Applicator Card & USB/SDIO Option	F
Applicator Card & Wireless B/G Option	K
Applicator Card, Wireless B/G Option & USB/SDIO	M
Internal LAN & Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
Wireless B/G Option	S

Scanner/RFID Option

Do Not Include This Option	0
Linear Barcode Scanner	S
RFID Ready Option	Z

Misc. Options	
40mm Media Hub	6
3.0" Plastic Media Hub	7

H-6210 & H-6308

C	-	-	4							
---	---	---	---	--	--	--	--	--	--	--

Printer Model										
H-6210 - 6"-203 DPI, 10 IPS, Thermal Transfer Printer	82									
H-6308 - 6"-300 DPI, 8 IPS, Thermal Transfer Printer	93									
Custom Kit										
Datamax Standard Kit	00									
China Kit	07									
Direct Thermal/Thermal Transfer										
Bi-Directional Thermal Transfer	4									
A/C Power (Autorange Supply) Configuration and Cord										
No Power Cord Supplied	0									
220v: Black Power Cord With Straight-In European Plug	3									
220v: Black Power Cord With 90 Deg British Plug	4									
220v: Black Power Cords, British And European	6									
100v: Black Power Cord With Japanese Plug	7									
110v: Black Power Cord With U.S. Plug	8									
220v: Black Power Cord With South Africa Plug	9									
220v: Black Power Cord With Straight-In Swiss Plug	F									
220v: Black Power Cord With Straight-In Australian Plug	N									
220v: Black Power Cord With Straight-In Italian Plug	P									
220v: Black Power Cord With Israel Plug	U									
220v: Black Power Cord With Straight-In Argentinean Plug	W									
220v: Black Power Cord With Straight-In Chinese Plug	Y									
250v: Black Power Cord With Straight-In Brazil Plug	5									
Peel & Present and Internal Rewind Option										
No Internal Rewinder	0									
Present Sensor and No Internal Rewinder	1									
Internal Rewinder	4									
Present Sensor and Internal Rewinder	6									
Basic Peel, Present & Internal Rewind	E									
Cutter Option										
Do Not Include This Option	0									
Standard Cutter	4									
Font Expansion Option										
Do Not Include This Option	0									
PL-Z Emulation	1									
PL-I Emulation	2									
Kanji Gothic B Font	H									
Simplified Chinese Font	N									
Korean Hangul Font	V									
PL-Z Emulation and Kanji Font	P									
PL-Z Emulation and Chinese Font	Q									
Interface Options										
Do Not Include This Option	0									
Applicator Card Kit	P									
Applicator Card & USB/SDIO Option	F									
Applicator Card & Wireless B/G Option	K									
Applicator Card, Wireless B/G Option & USB/SDIO	M									
Internal LAN & Wireless B/G & USB/SDIO Option	J									
USB & SDIO Option	E									
Wireless B/G Option	S									
Scanner/RFID Option										
Do Not Include This Option	0									
Linear Barcode Scanner	S									
RFID Ready Option	Z									
Misc. Options										
3.0" Metal Media Hub	4									
Static Brush Kit	L									

H-4212X, H-4310X & H-4606X

C - - 4

Printer Model

H-4212X - 4"-203 DPI, 12 IPS, Thermal Transfer Printer	32
H-4310X - 4"-300 DPI, 10 IPS, Thermal Transfer Printer	33
H-4606X - 4"-600 DPI, 6 IPS, Thermal Transfer Printer	46

Custom Kit

Datamax Standard Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Aurorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Cast Peel & Present Option and Internal Rewind	9
Basic Peel & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Applicator Card Kit	P
Applicator Card & Wireless B/G Option	K
Wireless B/G	S

Scanner/Rfid Option

Do Not Include This Option	0
Linear Barcode Scanner	S
RFID Ready Option	Z

Misc. Options

3.0" Metal Media Hub	4
40mm Media Hub	6

H-6212X & H-6310X

C - - 4

Printer Model

H-6212X - 6"-203 DPI, 12 IPS, Thermal Transfer Printer	62
H-6310X - 6"-300 DPI, 10 IPS, Thermal Transfer Printer	63

Custom Kit

Datamax Standard Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Basic Peel, Present & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Applicator Card Kit	P
Applicator Card & Wireless B/G Option	K
Wireless B/G	S

Scanner/RFID Option

Do Not Include This Option	0
Linear Barcode Scanner	S
RFID Ready Option	Z

Misc. Options

3.0" Metal Media Hub	4
----------------------	---

H-8308X

C - - 4 - - - - - 4

Printer Model

H-8308X - 8"-300 DPI, 8 IPS, Thermal Transfer Printer 83

Custom Kit

Datamax Standard Kit 00
China Kit 07

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer 4

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied 0
220v: Black Power Cord With Straight-In European Plug 3
220v: Black Power Cord With 90 Deg British Plug 4
220v: Black Power Cords, British And European 6
100v: Black Power Cord With Japanese Plug 7
110v: Black Power Cord With U.S. Plug 8
220v: Black Power Cord With South Africa Plug 9
220v: Black Power Cord With Straight-In Swiss Plug F
220v: Black Power Cord With Straight-In Australian Plug N
220v: Black Power Cord With Straight-In Italian Plug P
220v: Black Power Cord With Israel Plug U
220v: Black Power Cord With Straight-In Argentinean Plug W
220v: Black Power Cord With Straight-In Chinese Plug Y
250v: Black Power Cord With Straight-In Brazil Plug 5

Peel & Present and Internal Rewind Option

No Internal Rewinder 0
Present Sensor and No Internal Rewinder 1
Internal Rewinder 4
Present Sensor and Internal Rewinder 6
Basic Peel, Present & Internal Rewind E

Cutter Option

Do Not Include This Option 0
Standard Cutter 4

Font Expansion Option

Do Not Include This Option 0
PL-Z Emulation 1
PL-I Emulation 2
Kanji Gothic B Font H
Simplified Chinese Font N
Korean Hangul Font V
PL-Z Emulation and Kanji Font P
PL-Z Emulation and Chinese Font Q

Interface Options

Do Not Include This Option 0
Applicator Card Kit P
Applicator Card & Wireless B/G Option K
Wireless B/G S

Scanner/RFID Option

Do Not Include This Option 0
Linear Barcode Scanner S

Misc. Options

3.0" Metal Media Hub 4

I-4212e, I-4310e, & I-4606e

I	-	-								0	
Printer Model											
I-4212e 4" - 203DPI/12IPS Printer w/graphic display											12
I-4310e 4" - 300DPI/10IPS Printer w/graphic display											13
I-4606e 4" - 600DPI/6IPS Printer w/graphic display											16
Custom Kit											
Datamax Kit											00
China Kit											07
Direct Thermal/Thermal Transfer											
Direct Thermal											0
Bi-Directional Thermal Transfer											4
A/C Power (Aurorange Supply) Configuration and Cord											
No Power Cord Supplied											0
220v: Black Power Cord With Straight-In European Plug											3
220v: Black Power Cord With 90 Deg British Plug											4
220v: Black Power Cords, British And European											6
100v: Black Power Cord With Japanese Plug											7
110v: Black Power Cord With U.S. Plug											8
220v: Black Power Cord With South Africa Plug											9
220v: Black Power Cord With Straight-In Swiss Plug											F
220v: Black Power Cord With Straight-In Australian Plug											N
220v: Black Power Cord With Straight-In Italian Plug											P
220v: Black Power Cord With Israel Plug											U
220v: Black Power Cord With Straight-In Argentinean Plug											W
220v: Black Power Cord With Straight-In Chinese Plug											Y
250v: Black Power Cord With Straight-In Brazil Plug											5
Peel & Present and Internal Rewind Option											
No Internal Rewinder											0
Internal Rewinder											4
Cast Peel & Present Option and Internal Rewind											9
Cutter Option											
Do Not Include This Option											0
Standard Cutter (10mil)											4
Font Expansion Option											
Auto Detect: DPL, PLZ & PLI											0
Kanji Gothic B Font											H
Simplified Chinese											N
Korean Hangul Font											V
Interface Options											
Base Model (includes 64MB Flash, 32MB RAM, Serial, Parallel, & USB)											0
Base Model w/Wired & Wireless LAN											C
Base Model w/USB Host & SDIO Slot											E
Base Model w/Wired LAN											L
Base Model w/GPIO Interface Card											P
Base Model w/Wired & Wireless LAN & USB Host & SDIO Slot											T
Base Model w/Wired LAN & GPIO Interface Card											X
Not Used											
Do Not Include This Option											0
Misc. Options											
Fixed Media Hanger (Max speed 8ips)											0
3.0"/1.5" Media Hub											7
40mm Media Hub											6

M-4206, M-4210, & M-4308

K - - - - - 0

Printer Model

M-4206 - 4"-203 DPI, 6 IPS, Printer with Graphic Display	D2
M-4210 - 4"-203 DPI, 10 IPS, Printer with Graphic Display	J2
M-4308 - 4"-300 DPI, 8 IPS, Printer with Graphic Display	A3

Custom Kit

Datamax Kit	00
China Kit	07

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Internal Rewinder	4
Cast Peel & Present Option and Internal Rewind	9
Cast Peel & Present Option w/Center Sensor and Internal Rewind	8

Cutter Option

Do Not Include This Option	0
Standard Cutter (10mil)	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Internal LAN Option	Y
Internal LAN & Wireless B/G	S

Scanner/RFID Option

Do Not Include This Option	0
----------------------------	---

Misc. Options

Fixed Media Hanger	0
40mm Media Hub	6
3.0" Media Hub	7

MP Compact4 Mark II

X - 00 - 0

Printer Model

MP Compact4 200 DPI	A1
MP Compact4 300 DPI	A2
MP Compact4 200 DPI WIRELESS	A3
MP Compact4 200 DPI W/150mm Label Roll Support	A5
MP Compact4 300 DPI W/150mm Label Roll Support	A6
MP Compact4 200 DPI WIRELESS W/150mm Label Roll Support	A7
MP Compact4 300 DPI WIRELESS W/150mm Label Roll Support	A8
MP Compact4 200 DPI W/PEEL-OFF KIT	A9
MP Compact4 200 DPI WIRELESS W/PEEL-OFF KIT	B0
MP Compact4 200 DPI WIRELESS W/LTS KIT	B2
MP Compact4 200 DPI W/CUTTER	B3
MP Compact4 300 DPI W/CUTTER	B4
MP Compact4 200 DPI WIRELESS W/CUTTER	B5
MP Compact4 200 DPI W/LTS KIT & 150mm Label Roll Support	B7
MP Compact4 200 DPI WIRELESS W/LABELROLL & LTS	B8
MP Compact4 200 DPI W/PEELOFF & LTS KIT	B9
MP Compact4 300 DPI W/PEELOFF & LTS KIT	C0
MP Compact4 200 DPI WIRELESS W/PEELOFF & LTS KIT	C1
MP Compact4 300 DPI WIRELESS W/PEELOFF & LTS KIT	C2

Custom Kit

MP Compact4 Kit	00
-----------------	----

Not Used

Do Not Include This Option	0
----------------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
Power Cord with European Plug	3
Power Cord with British Plug	4
Power Cord with U.S. & Canada Plug	8
Power Cord with Swiss Plug	F
Power Cord with Denmark Plug	W
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used

Do Not Include This Option	0
----------------------------	---

Not Used

Do Not Include This Option	0
----------------------------	---

Command Language Compatibility

Label Point w/o emulation (Standard)	0
DPL w/ PLZ emulation	1
DPL w/ PLI emulation	2
DPL w/ PLB emulation	3
DPL w/o emulation	4

Interface Options

Do Not Include This Option	0
Parallel to Serial Cable	6
USB Cable	U

Not Used

Do Not Include This Option	0
----------------------------	---

Misc. Options

Do Not Include This Option	0
Wall-Mount Kit (<i>not available with Peel-Off option</i>)	B

MP Compact4 Mobile Mark II

X - 00 - 0

Printer Model

MP Compact4 Mobile 200 DPI	D1
MP Compact4 Mobile 300 DPI	D2
MP Compact4 Mobile 200 DPI WIRELESS	D3
MP Compact4 Mobile 300 DPI WIRELESS	D4
MP Compact4 Mobile 200 DPI W/PEEL-OFF KIT	D5
MP Compact4 Mobile 200 DPI WIRELESS W/LTS KIT	D8
MP Compact4 Mobile 200 DPI W/PEELOFF & LTS	D9
MP Compact4 Mobile 200 DPI WIRELESS W/PEELOFF & LTS	E0

Custom Kit

MP Compact4 Mobile Kit	00
------------------------	----

Not Used

Do Not Include This Option	0
----------------------------	---

A/C Power (Aurorange Supply) Configuration and Cord

DC Power Cable	7
----------------	---

Not Used

Do Not Include This Option	0
----------------------------	---

Not Used

Do Not Include This Option	0
----------------------------	---

Command Language Compatibility

Label Point w/o emulation (Standard)	0
DPL w/ PLZ emulation	1
DPL w/ PLI emulation	2
DPL w/ PLB emulation	3
DPL w/o emulation	4

Interface Options

Do Not Include This Option	0
Parallel to Serial Cable	6
USB Cable	U

Not Used

Do Not Include This Option	0
----------------------------	---

Misc. Options

Do Not Include This Option	0
----------------------------	---

MP Nova 4 & 6

X		-	00	-							0	
---	--	---	----	---	--	--	--	--	--	--	---	--

Printer Model	
MP NOVA 4 DT 200 Printer Kit	41
MP NOVA 4 TT 200 Printer Kit	42
MP NOVA 4 TT 300 Printer Kit	44
MP NOVA 4 DT 200 PRT W/Peel-Off Kit & LTS	45
MP NOVA 4 DT 200 PRT W/215mm Kit	48
MP NOVA 4 DT 200 PRT W/Big Roll P-O & LTS	49
MP NOVA 4 TT 200 PRT W/P-O & LTS	51
MP NOVA 4 TT 300 PRT W/P-O & 215mm	52
MP NOVA 6 DT 200 Printer Kit	61
MP NOVA 6 TT 200 Printer Kit	62
MP NOVA 6 TT 200 PRT W/215MM Kit	63
MP NOVA 6 DT 200 PRT W/Peel-Off Kit & LTS	65
MP NOVA 6 TT 200 PRT W/Peel-Off & LTS	66

Custom Kit	
Nova 4 Kit	00
Nova 6 Kit	00

Not Used	
Do Not Include This Option	0

A/C Power (Autorange Supply) Configuration and Cord	
No Power Cord Supplied	0
Power Cord with European Plug	3
Power Cord with British Plug	4
Power Cord with U.S. & Canada Plug	8
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used	
Do Not Include This Option	0

Not Used	
Do Not Include This Option	0

Not Used	
Do Not Include This Option	0

Interface Options	
Do Not Include This Option	0
Parallel to Serial Cable	6
Daisy-Chain Cable	D
USB Cable	U

Not Used	
Do Not Include This Option	0

Misc. Options	
Do Not Include This Option	0

Performance Series p1115s

P AD - 00 - 0 0

Printer Model

p1115s 4" - 600DPI / 6IPS Printer, USB & Ethernet

AD

Custom Kit

Datamax Standard Kit

00

China Kit

07

Direct Thermal/Thermal Transfer

Direct Thermal

0

Bi-Directional Thermal Transfer

4

A/C Power (Autorange Supply) Configuration and Cord

US Power Cord

8

UK & European Power Cord

6

Continental Europe Power Cord

3

UK & Ireland Power Cord

4

Denmark Power Cord

2

Switzerland Power Cord

F

220v: Black Power Cord With Straight-In Australian Plug

N

Italy Power Cord

P

India Power Cord

9

220V: Black Power Cord With Straight-In Chinese Plug

Y

Present Sensor/Rewinder Options

Do Not Include This Option

0

Present Sensor (Downward Looking)

1

Internal Rewinder

4

Internal Rewinder and Present Sensor (Downward Looking)

F

Internal Rewinder and Present Sensor (Upward Looking)

9

Cutter Option

Do Not Include This Option

0

Cutter

4

Font Expansion Option

Do Not Include This Option

0

Interface Option

GP I/O & Serial Port and 64MB Flash

C

GP I/O & Serial Port and 802.11b/g Wireless and 64MB Flash

D

GP I/O & Serial Port and USB Host and 64MB Flash

G

GP I/O & Serial Port and USB Host and 802.11b/g Wireless and 64MB Flash

H

USB Host and 64MB Flash

K

USB Host and 802.11b/g Wireless and 64MB Flash

L

64MB Flash

N

802.11b/g Wireless and 64MB Flash

P

Scanner/RFID Options

Do Not Include This Option

0

Misc. Options

Synchronized Media Hanger

4

3.0" Media Hub

0

1.0" Media Hub Kit

1

1.5" Media Hub Kit

2

3.0" Media Hub and Audio Alarm

5

1.0" Media Hub Kit and Audio Alarm

6

1.5" Media Hub Kit and Audio Alarm

7

Synchronized Media Hanger and Audio Alarm

8

Performance Series p1115

P AA - 00 - 0 0

Printer Model

p1115 4" - 300DPI / 6IPS Printer, USB & Ethernet

AA

Custom Kit

Datamax Standard Kit

00

China Kit

07

Direct Thermal/Thermal Transfer

Direct Thermal

0

Bi-Directional Thermal Transfer

4

A/C Power (Autorange Supply) Configuration and Cord

US Power Cord

8

UK & European Power Cord

6

Continental Europe Power Cord

3

UK & Ireland Power Cord

4

Denmark Power Cord

2

Switzerland Power Cord

F

220v: Black Power Cord With Straight-In Australian Plug

N

Italy Power Cord

P

India Power Cord

9

220V: Black Power Cord With Straight-In Chinese Plug

Y

Present Sensor/Rewinder Options

Do Not Include This Option

0

Present Sensor (Downward Looking)

1

Internal Rewinder

4

Internal Rewinder and Present Sensor (Downward Looking)

F

Internal Rewinder and Present Sensor (Upward Looking)

9

Cutter Option

Do Not Include This Option

0

Cutter

4

Font Expansion Option

Do Not Include This Option

0

Interface Option

Do Not Include This Option

0

GPIO & Serial Port

A

Scanner/RFID Options

Do Not Include This Option

0

Misc. Options

Synchronized Media Hanger

4

3.0" Media Hub

0

1.0" Media Hub Kit

1

1.5" Media Hub Kit

2

Performance Series p1120n

P AB - 00 - 0 0

Printer Model

p1120n 4" - 300DPI Near Edge / 8IPS Printer, USB & Ethernet

AB

Custom Kit

Datamax Standard Kit

00

China Kit

07

Direct Thermal/Thermal Transfer

Direct Thermal

0

Bi-Directional Thermal Transfer

4

A/C Power (Autorange Supply) Configuration and Cord

US Power Cord

8

UK & European Power Cord

6

Continental Europe Power Cord

3

UK & Ireland Power Cord

4

Denmark Power Cord

2

Switzerland Power Cord

F

220v: Black Power Cord With Straight-In Australian Plug

N

Italy Power Cord

P

India Power Cord

9

220V: Black Power Cord With Straight-In Chinese Plug

Y

Present Sensor/Rewinder Options

Do Not Include This Option

0

Present Sensor (Downward Looking)

1

Internal Rewinder

4

Internal Rewinder and Present Sensor (Downward Looking)

F

Internal Rewinder and Present Sensor (Upward Looking)

9

Cutter Option

Do Not Include This Option

0

Cutter

4

Font Expansion Option

Do Not Include This Option

0

Interface Option

Do Not Include This Option

0

GP I/O & Serial Port

A

GP I/O & Serial Port and 802.11b/g Wireless

B

GP I/O & Serial Port and 64MB Flash

C

GP I/O & Serial Port and 802.11b/g Wireless and 64MB Flash

D

GP I/O & Serial Port and USB Host

E

GP I/O & Serial Port and USB Host and 802.11b/g Wireless

F

GP I/O & Serial Port and USB Host and 64MB Flash

G

GP I/O & Serial Port and USB Host and 802.11b/g Wireless and 64MB Flash

H

USB Host

I

USB Host and 802.11b/g Wireless

J

USB Host and 64MB Flash

K

USB Host and 802.11b/g Wireless and 64MB Flash

L

802.11b/g Wireless

M

64MB Flash

N

802.11b/g Wireless and 64MB Flash

P

Scanner/RFID Options

Do Not Include This Option

0

Misc. Options

Synchronized Media Hanger

4

3.0" Media Hub

0

1.0" Media Hub Kit

1

1.5" Media Hub Kit

2

3.0" Media Hub and Audio Alarm

5

1.0" Media Hub Kit and Audio Alarm

6

1.5" Media Hub Kit and Audio Alarm

7

Synchronized Media Hanger and Audio Alarm

8

Performance Series p1125

P AC - 00 - 0 0

Printer Model

p1125 4" - 300DPI / 10IPS Printer, USB & Ethernet

AC

Custom Kit

Datamax Standard Kit

00

China Kit

07

Direct Thermal/Thermal Transfer

Direct Thermal

0

Bi-Directional Thermal Transfer

4

A/C Power (Autorange Supply) Configuration and Cord

US Power Cord

8

UK & European Power Cord

6

Continental Europe Power Cord

3

UK & Ireland Power Cord

4

Denmark Power Cord

2

Switzerland Power Cord

F

220v: Black Power Cord With Straight-In Australian Plug

N

Italy Power Cord

P

India Power Cord

9

220V: Black Power Cord With Straight-In Chinese Plug

Y

Present Sensor/Rewinder Options

Do Not Include This Option

0

Present Sensor (Downward Looking)

1

Internal Rewinder

4

Internal Rewinder and Present Sensor (Downward Looking)

F

Internal Rewinder and Present Sensor (Upward Looking)

9

Cutter Option

Do Not Include This Option

0

Cutter

4

Font Expansion Option

Do Not Include This Option

0

Interface Option

Do Not Include This Option

0

GP I/O & Serial Port

A

GP I/O & Serial Port and 802.11b/g Wireless

B

GP I/O & Serial Port and 64MB Flash

C

GP I/O & Serial Port and 802.11b/g Wireless and 64MB Flash

D

GP I/O & Serial Port and USB Host

E

GP I/O & Serial Port and USB Host and 802.11b/g Wireless

F

GP I/O & Serial Port and USB Host and 64MB Flash

G

GP I/O & Serial Port and USB Host and 802.11b/g Wireless and 64MB Flash

H

USB Host

I

USB Host and 802.11b/g Wireless

J

USB Host and 64MB Flash

K

USB Host and 802.11b/g Wireless and 64MB Flash

L

802.11b/g Wireless

M

64MB Flash

N

802.11b/g Wireless and 64MB Flash

P

Scanner/RFID Options

Do Not Include This Option

0

Misc. Options

Synchronized Media Hanger

4

3.0" Media Hub

0

1.0" Media Hub Kit

1

1.5" Media Hub Kit

2

3.0" Media Hub and Audio Alarm

5

1.0" Media Hub Kit and Audio Alarm

6

1.5" Media Hub Kit and Audio Alarm

7

Synchronized Media Hanger and Audio Alarm

8

A-4212, A-4310, A-4408, & A-4606**Please refer to your supplier for Printer Model pricing**

L - - - - - R

Printer Model

Right Hand, A-4212E 8MB FLASH	A2
Right Hand, A-4310E 8MB FLASH	A3
Right Hand, A-4408E 8MB FLASH	A4
Right Hand, A-4606E 8MB FLASH	A6
Left Hand, A-4212E 8MB FLASH	B2
Left Hand, A-4310E 8MB FLASH	B3
Left Hand, A-4408E 8MB FLASH	B4
Left Hand, A-4606E 8MB FLASH	B6

Custom Kit

Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Serbia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used

Do not Include this Option	0
----------------------------	---

Cutter / Ribbon Saver / Top Pinch Roller Option

Do Not Include This Option	0
Top Pinch Roller Option	5
Ribbon Saver and Top Pinch Roller Option	C

Font Expansion Option

Do Not Include This Option	0
Kanji Gothic B	H
Simplified Chinese	N
Korean Hangul Font	V

Interface Options

Do Not Include This Option	0
DMXrNet III Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
DMXrNet III Wireless B/G Option	S

RFID

UHF 915MHz MP RFID Option	R
Misc. Options	
Do Not Include This Option	0
Remote Display Option	F
Remote Display "Ready" Option	G
Cover Open Sensor	V
Remote Display Option & Cover Open Sensor	X
Remote Display "Ready" Option & Cover Open Sensor	Z

A-6212 & A-6310

Please refer to your supplier for Printer Model pricing

Printer Model

Right Hand, A-6212E 8MB FLASH	C2
Right Hand, A-6310E 8MB FLASH	C3
Left Hand, A-6212E 8MB FLASH	D2
Left Hand, A-6310E 8MB FLASH	D3

Custom Kit

Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Serbia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Aurorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Not Used

Do not Include this Option	0
----------------------------	---

Ribbon Saver / Top Pinch Roller Option

Do Not Include This Option	0
Top Pinch Roller Option	5
Ribbon Saver and Top Pinch Roller Option	C

Font Expansion Option

Do Not Include This Option	0
Kanji Gothic B	H
Simplified Chinese	N
Korean Hangul Font	V

Interface Options

Do Not Include This Option	0
DMXrfNet III Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
DMXrfNet III Wireless B/G Option	S

RFID

UHF 915MHz MP RFID Option	R
---------------------------	---

Misc. Options

Do Not Include This Option	0
Remote Display Option	F
Remote Display "Ready" Option	G
Cover Open Sensor	V
Remote Display Option & Cover Open Sensor	X
Remote Display "Ready" Option & Cover Open Sensor	Z

H-4212, H-4310, H-4408, & H-4606

C		-		-	4							
---	--	---	--	---	---	--	--	--	--	--	--	--

Printer Model

H-4212 - 4"-203 DPI, 12 IPS, Thermal Transfer Printer	42
H-4310 - 4"-300 DPI, 10 IPS, Thermal Transfer Printer	43
H-4408 - 4"-400 DPI, 8 IPS, Thermal Transfer Printer	34
H-4606 - 4"-600 DPI, 6 IPS, Thermal Transfer Printer	36

Custom Kit

Datamax RFID HF Kit	J2
Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Serbia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Aurorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Cast Peel & Present Option and Internal Rewind	9
Basic Peel & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Applicator Card Kit	P

Applicator Card & USB/SDIO Option	F	
Applicator Card & Wireless B/G Option	K	
Applicator Card, Wireless B/G Option & USB/SDIO	M	
Internal LAN & Wireless B/G & USB/SDIO Option	J	
USB & SDIO Option	E	
Wireless B/G Option	S	
Scanner/RFID Option		
RFID HF (for J2 kit only)	R	
RFID UHF	V	
Misc. Options		
40mm Media Hub		6
3.0" Plastic Media Hub		7

H-6210 & H-6308

C - 4

Printer Model

H-6210 - 6"-203 DPI, 10 IPS, Thermal Transfer Printer	82
H-6308 - 6"-300 DPI, 8 IPS, Thermal Transfer Printer	93

Custom Kit

Datamax RFID HF Kit	J2
Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Sebia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Basic Peel, Present & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
----------------------------	---

Applicator Card Kit	P
Applicator Card & USB/SDIO Option	F
Applicator Card & Wireless B/G Option	K
Applicator Card, Wireless B/G Option & USB/SDIO	M
Internal LAN & Wireless B/G & USB/SDIO Option	J
USB & SDIO Option	E
Wireless B/G Option	S

Scanner/RFID Option

RFID HF (for J2 kit only)	R
RFID UHF	V

Misc. Options

3.0" Metal Media Hub	4
Static Brush Kit	L

H-4212X, H-4310X & H-4606X

C		-		-	4							
---	--	---	--	---	---	--	--	--	--	--	--	--

Printer Model

H-4212X - 4"-203 DPI, 12 IPS, Thermal Transfer Printer	32
H-4310X - 4"-300 DPI, 10 IPS, Thermal Transfer Printer	33
H-4606X - 4"-600 DPI, 6 IPS, Thermal Transfer Printer	46

Custom Kit

Datamax RFID HF Kit	J2
Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Serbia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Cast Peel & Present Option and Internal Rewind	9
Basic Peel & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options		
Do Not Include This Option	0	
Applicator Card Kit	P	
Applicator Card & Wireless B/G Option	K	
Wireless B/G	S	
Scanner/RFID Option		
RFID HF (for J2 kit only)	R	
RFID UHF	V	
Misc. Options		
3.0" Plastic Media Hub		4
40mm Media Hub		6

H-6212X & H-6310X

C - - 4 - - - - - 4

Printer Model

H-6212X - 6"-203 DPI, 12 IPS, Thermal Transfer Printer	62
H-6310X - 6"-300 DPI, 10 IPS, Thermal Transfer Printer	63

Custom Kit

Datamax RFID HF Kit	J2
Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Serbia, France, Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugal, Spain, Sweden & Slovak Republic)	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2

Direct Thermal/Thermal Transfer

Bi-Directional Thermal Transfer	4
---------------------------------	---

A/C Power (Aurorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Present Sensor and No Internal Rewinder	1
Internal Rewinder	4
Present Sensor and Internal Rewinder	6
Basic Peel, Present & Internal Rewind	E

Cutter Option

Do Not Include This Option	0
Standard Cutter	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
----------------------------	---

Applicator Card Kit	P
Applicator Card & USB/SDIO Option	F
Applicator Card & Wireless B/G Option	K
Scanner/RFID Option	
RFID HF (for J2 kit only)	R
RFID UHF	V
Misc. Options	
3.0" Metal Media Hub	4
Static Brush Kit	L

M-4210 & M-4308

K - - - - - 0

Printer Model

M-4210 - 4"-203 DPI, 10 IPS, Printer with Graphic Display	J2
M-4308 - 4"-300 DPI, 8 IPS, Printer with Graphic Display	A3

Custom Kit

Datamax RFID HF Kit	J2
Datamax RFID MP FCC/IC Kit (For Use In U.S. And Canada)	L1
Datamax RFID MP 302 - 208 Kit (For Use In Germany, Denmark, Finland, Iceland, Switzerland, Cyprus, United Kingdom, Malta, Sebia, France,Bulgaria, Slovenia, Poland, Lithuania, Estonia, Czech, Republic, Luxembourg, Greece, Netherlands, Ireland, Belgium, Hungary, Italy, Norway, Portugugal, Spain, Sweden & Slovak Republic	L2
Datamax RFID MP Kit (For Use In Australia, Hong Kong, Thailand, & Singapore)	L5
Datamax RFID MP Kit (For Use In New Zealand)	L6
Datamax RFID MP Kit (For Use In Israel)	L7
Datamax RFID MP Kit Japan Kit	L8
Datamax RFID MP Kit Korea Kit	L9
Datamax RFID MP Kit India Kit	R1
Datamax RFID MP Kit Taiwan Kit	R2
Datamax RFID MP Kit Brazil Kit (M-4210 only)	R3
Datamax RFID MP Kit China Kit (M-4308 only)	R4

Direct Thermal/Thermal Transfer

Direct Thermal	0
Bi-Directional Thermal Transfer	4

A/C Power (Aurorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
100v: Black Power Cord With Japanese Plug	7
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
220v: Black Power Cord With Straight-In Argentinean Plug	W
220v: Black Power Cord With Straight-In Chinese Plug	Y
250v: Black Power Cord With Straight-In Brazil Plug	5

Peel & Present and Internal Rewind Option

No Internal Rewinder	0
Internal Rewinder	4
Cast Peel & Present Option and Internal Rewind	9

Cutter Option

Do Not Include This Option	0
Standard Cutter (10mil)	4

Font Expansion Option

Do Not Include This Option	0
PL-Z Emulation	1
PL-I Emulation	2
Kanji Gothic B Font	H
Simplified Chinese Font	N
Korean Hangul Font	V
PL-Z Emulation and Kanji Font	P
PL-Z Emulation and Chinese Font	Q

Interface Options

Do Not Include This Option	0
Internal LAN Option	Y
Internal LAN & Wireless B/G	S

Scanner/RFID Option

RFID HF	R	
RFID UHF	V	
Misc. Options		
Fixed Media Hanger		0
40mm Media Hub		6
3.0" Media Hub		7

ST-3210 & ST-3306

Q - 00 - 0

Printer Model

ST-3210 Printer 203DPI, 6MB FLASH	52
ST-3306 Printer 300DPI, 6MB FLASH	53

Custom Kit

ST-3210, 203 DPI Kit	00
ST-3210, 203 DPI KIT w/Multi-Lang Manual	01
ST-3306, 300 DPI Kit	00
ST-3306, 300 DPI KIT w/Multi-Lang Manual	01

Direct Thermal/Thermal Transfer

Direct Thermal Only	0
---------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
250v: Black Power Cord With Straight-In Brazil Plug	5

Media Hub Option

Do Not Include This Option	0
Media Roll Support	B

ILPC Font Options

Do Not Include This Option	0
ILPC - CG Times Only Font - download	A
ILPC - CG Times Font Family (requires Printer Model 52 or 53)	G
Korean Font Option (requires Printer Model 52 or 53)	V
Simplified Chinese Option (requires Printer Model 52 or 53)	N

Printer Programming Language Setting

DTPL (Boca Emulation)	0
DPL	1
Auto Detect	2

Not Used

Do Not Include This Option	0
----------------------------	---

Lock Sets

Lock Set, Keyed Different, No Master Key	0
Lock Set, Keyed Different, With Master Key	A
Lock Set, Keyed Alike	B

Misc. Options

No Cutter With Standard TOF Sensor	0
Cutter Kit With Standard TOF Sensor & 3.25" Ticket Tray	2
Cutter Kit With TOF, Top Sensor & 3.25" Ticket Tray	8
No Cutter With TOF, Top Sensor	M
Cutter Kit With Standard TOF Sensor & 2" Ticket Tray	P
Cutter Kit With TOF, Top Sensor & 2" Ticket Tray	Q

SV-3210 & SV-3306

Q - 00 - - - - - 0

Printer Model

SV-3210 Printer 203DPI, 6MB FLASH	92
SV-3306 Printer 300DPI, 6MB FLASH	93

Custom Kit

SV-3210, 203 DPI Kit	00
SV-3210, 203 DPI KIT w/Multi-Lang Manual	01
SV-3306, 300 DPI Kit	00
SV-3306, 300 DPI KIT w/Multi-Lang Manual	01

Direct Thermal/Thermal Transfer

Direct Thermal Only	0
---------------------	---

A/C Power (Autorange Supply) Configuration and Cord

No Power Cord Supplied	0
220v: Black Power Cord With Straight-In European Plug	3
220v: Black Power Cord With 90 Deg British Plug	4
220v: Black Power Cords, British And European	6
110v: Black Power Cord With U.S. Plug	8
220v: Black Power Cord With South Africa Plug	9
220v: Black Power Cord With Straight-In Swiss Plug	F
220v: Black Power Cord With Straight-In Australian Plug	N
220v: Black Power Cord With Straight-In Italian Plug	P
220v: Black Power Cord With Israel Plug	U
250v: Black Power Cord With Straight-In Brazil Plug	5

Media Hub Option

Do Not Include This Option	0
----------------------------	---

ILPC Font Options

Do Not Include This Option	0
ILPC - CG Times Only Font - download	A
ILPC - CG Times Font Family (requires Printer Model 52 or 53)	G
Korean Font Option (requires Printer Model 52 or 53)	V
Simplified Chinese Option (requires Printer Model 52 or 53)	N

Printer Programming Language Setting

DTPL (Boca Emulation)	0
DPL	1
Auto Detect	2

Not Used

Do Not Include This Option	0
----------------------------	---

Not Used

Do Not Include This Option	0
----------------------------	---

Misc. Options

Assy, Tearbar - Standard TOF Sensor	0
Assy, Cutter, Ticket Present - Standard TOF Sensor	2
No Option	N
Assy, Tearbar - Top TOF Sensor	Y
Assy, Cutter, Ticket Present - Top TOF Sensor	Z

Workstation Series w1110

W - 00 - 0 0 0 0 0

Printer Model

w1110 4" - 300DPI / 4IPS Printer (w/New Power Supply)

CB

Custom Kit

Datamax Standard Kit

00

Direct Thermal/Thermal Transfer

Direct Thermal Option

0

Power Cord Options

US Power Cord

J

UK & European Power Cord

E

Continental Europe Power Cord

L

UK & Ireland Power Cord

K

Switzerland Power Cord

M

Italy Power Cord

V

Autoranging Power Supply With Australian Power Cord

T

South Africa

B

Present Sensor Option

Do Not Include This Option

0

Peel & Present Option

P

Cutter Option

Do Not Include This Option

0

Font Expansion Option

Do Not Include This Option

0

Interface Options

Do Not Include This Option

0

Serial Port

1

Not Used

Do Not Include This Option

0

Misc. Options

1" & 1.5" Media Hanger

0

1" & 1.5" Media Hanger and Cover Lock

L