

HCH-9060-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
 32°F to 104°F

Storage Range: -10°C to 50°C
 14°F to 122°F

Dimensions:

Length: 660 mm
 Width: 160 mm
 Height: 89 mm
 Weight: 2500 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



GTS Battery

HMC9000-Li(24)

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.03.28

Compact and Versatile Six Bay Charger for MC9000 Series Devices

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies and cable.

Dual-chemistry charger
 Supports Li-Ion and Li-Polymer chemistries.



More charging in less space
 Charges 50% more batteries in same space as OEM charger.

Tri-color charging indications
 A charging LED indicates charging status.



Hassle-free mounting
 Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

