

SII



Seiko Instruments U.S.A., Inc.



MP-A40 SERIES MOBILE PRINTERS

Rugged and Reliable Printing.
Simple Operation. Stylish Design.



Product Highlights:

- Ability to withstand multiple drops from up to 6.6 feet.
- High-resolution receipts at 100 mm/second.
- Stylish (yet rugged) design.
- Compatible with the latest operating systems, including Windows 10.
- Handles up to a 4" paper width, and weighs 1.5 pounds.

Rugged and Reliable Printing

With the ability to withstand multiple drops from up to 6.6 feet (2 meters), the MP-A40 Series Mobile Printers are known for their highest level print speeds currently available on the market. Imagine being able to print high-resolution receipts at 100 mm per second! What's more is after several tests performed in our product lab, the MP-A40 mobile printer was able to perform at 100% after multiple drops.

Simple Operation, Stylish Design

With up to a 4-inch paper width, and weighing a little more than 1.5 pounds, the MP-A40 Series mobile printers are built tough, but that doesn't mean they lack in style or simplicity. With intuitive drop-in paper setting and easy access button, the printers offer a smart and robust design that fit into the palm of your hand, or belt clip; a small carry-on case offers the option of over-the-shoulder transport.

Technology Options

The MP-A40 Series Mobile Printers offer compatibility with the latest operating systems including Windows, 7, 8, 8.1 and 10. There is also SDK availability for both Android and Windows CE print class libraries for added mobility. The printers also offer auto-detection Bluetooth interface and Wi-Fi capabilities, providing added value and easy transition from cable to wireless communications.

Technical Specifications

Model		MP-A40 Series Mobile Printer
Printing	Resolution (dots/mm)	8
	Speed (mm/sec)	105 (4-inch)
Media	Paper Width (mm)	80/100/105/112 *with fixing plater
	Paper Form	Roll
	Roll Diameter (mm)	58
	Paper Type	Thermal/Thermal Label
Interface	Wire	USB
	Wireless	Bluetooth v2.1 +EDR or W-LAN 802.11.a/b/g/n
Command		ESC-POS/CPCL/markup language (HTML)
Drop ¹		2.0m (6.6 feet) multiple drop
Operating Temp (C)		-20 to 50
Storage Temp (C)		-30 to 70
IP rating ¹		IP54
Battery (option)		7.2V / 2000mAh (high-rate)
Size (mm)		W156xD152.1 xH71
Weight (g), w/battery, w/o paper		750
Accessories		AC adapter, battery, AC cable, USB cable, battery charger, quad battery charger, cigarette socket charger, strap

*1 Test result by SII condition



Seiko Instruments U.S.A., Inc.

21221 S. Western Avenue, Suite 250
Torrance, CA 90501
Telephone (310) 517-7778
Facsimile (310) 517-8154
Email: printerinfo@seikoinstruments.com
www.siiprinters.com