



ZEBRA

ZEBRA 9160 G2

THE FLEXIBLE WIRELESS GATEWAY FOR MOBILE PRODUCTIVITY

You need to manage and track inventory in some of the most challenging outdoor environments — from seaports and rail yards to airports and expansive outdoor manufacturing yards. Not only are these areas vast, but materials are often present that can wreak havoc on a traditional Wi-Fi signal, from large metal shipping containers to water, wood, ceramics, microwave dryers, other 2.4 GHz wireless networks and more. The 9160 G2 wireless gateway solves that problem with Narrowband wireless connectivity. Narrowband provides a robust and secure wireless connection for simple data applications that can cost-effectively cover every inch of your sprawling facility. Just one 9160 G2 base station covers up to one mile — a distance that would typically require 10 Wi-Fi access points. And since our advanced network and data protocols overcome Narrowband bandwidth constraints, your workers get sub-second access to the information they need to accurately and efficiently move inventory in, through and out of your facility. Get affordable wireless connectivity for your largest spaces with Narrowband, only from Zebra.

Easy, cost-effective wireless coverage in every inch of your facility

Narrowband is ideal for your largest, most expansive areas, minimizing infrastructure requirements and cost while delivering a solid dependable connection in challenging RF environments. Regardless of the types of materials or volume of traffic in the 2.4 GHz band that are present in your environment, they will not degrade the signal. And since the mobile devices connected to your narrowband network operate in low power receive mode, the resulting substantial energy savings ensures that your workers have plenty of power for a full-shift.

Flexible backhaul options

The 9160 G2 offers wired and wireless options to connect to your network. You can connect the 9160 G2 to your network with a single Ethernet cable — with support for Power-over-Ethernet, there is no need to run power. The optional Wi-Fi 802.11a/b/g radio provides a wireless connection to your network, addressing areas where running a cable is too challenging or expensive. And the wide variety of indoor and outdoor 2.4 GHz and 5 GHz directional and sector panel antennas ensure a robust wireless connection back to your enterprise network.

Easy remote management

Centralized and remote management of security, configuration profiles and software upgrades makes network management easy.

A total solution

In addition to the 9160 G2, you'll need devices that can run on the Narrowband network. That's why our Omnii XT15 handheld and VH10 vehicle mount mobile computers offer Narrowband radio options. These rugged devices are ready for the toughest environmental conditions. And whether workers are on foot or driving a forklift or other material handling vehicle, there is a device option that is perfect for the job.

COST-EFFECTIVE, ROBUST WIRELESS CONNECTIVITY FOR YOUR MOST EXPANSIVE AREAS

WHERE IS THE 9160 G2 AT HOME?

Indoor environments

- Suitable for rugged warehouse and manufacturing applications with any type of coverage pattern

Outdoor environments

- A variety of high gain antenna and wired or wireless (WDS) backhaul options make the 9160 G2 a great choice for outdoor port and yard applications

Specialty environments: refrigerated

- Dual radio operation and antenna splitting allows for coverage of isolated refrigerated sections from a single access point

Environments that require Multiple SSIDs

- Allows you to easily divide the WLAN into virtual wireless LANs, with VLAN support for different applications and different user types.

For more information, please visit www.zebra.com/9160g2

TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS		SECURITY
Dimensions	14.3 in. L x 10.3 in. W x 2.9 in. D 363 mm L x 262 mm W x 74 mm D	802.1x authentication MAC filtering WPA 1 (TKIP encryption) WPA 2 (802.11i, AES encryption) Inhibit/Ignore SSID Broadcast User-based access control via embedded Radius authentication server (PEAP with 8 APIs or less)
Weight	6.5 lbs./2.9 kg	
Network Interface	10/100 Base-T with auto-negotiation, half and full duplex	
Diagnostic/ Configuration Terminal Interface	RS232 port for debug and diagnostics supporting configuration and firmware update SNMP support (compatible with MapRF) Telnet to Console HTTP Web Browser Management Interface	
Power	100 – 240VAC, 50/60Hz, 1A	
Power-over-Ethernet (PoE)	802.3af compliant, 48VDC nominal	
Visual Indicators	LED 1 - on solid when Ethernet link present LED 2 - blinks for rx/tx Ethernet traffic LED 3 - blinks for rx/tx radio 1 traffic LED 4 - blinks for rx/tx radio 2 traffic LED 5 - always off (unused at this time) LED 6 - on solid	
PERFORMANCE CHARACTERISTICS		ADVANCED FEATURES
CPU	Intel IXP420 processor at 266MHz	Wireless Distribution System (WDS) Load balancing Multiple SSIDs/BSSIDs, Virtual Wireless Networks (VWNs) Support of 802.1Q protocol Mini-controller capabilities for thin client devices featuring VTxx, 5250 and 3274 emulations
Memory	16MB Flash, 32MB SDRAM	
USER ENVIRONMENT		SERVICES AND SUPPORT
Operating Temp.	0°C to +55° C / 32°F to +151°F	Service from the Start Primary: A unique service that covers normal wear and tear as well as accidental damage to internal and external components. Includes a collection option with pre-paid ground freight on return shipments.
Storage Temp.	0°C to +70° C / 32° F to +158° F	
Humidity	10% to 90% non-condensing	
Sealing	IP42	
Vibration	EH0002 (shipping vibration only)	
Integrated Sensors	Motion (accelerometer); digital compass	
Reliability	MTBF 25,000 Hours (MIL-HDBK-217F)	
WIRELESS DATA COMMUNICATIONS		REGULATORY
		USA FCC part 15, subpart B, class B (unintentional radiated emission) UL601950, 2000 Bi-Nat (electrical safety) (* Note: NRTL/C done by CSA covers UL 1950 bi-national standards)
		Canada ICES-003 / CSA C108.8-M1983 (unintentional radiated emission); CSA 950 CSA-C22.2 No. 950-M98 (electrical safety)(* Note: FCC part 15, subpart B covers ICES-003 / CSA C108.8-M1983)
		European (CE Mark) 73/23/EEC Low Voltage Directive: TUV & CB EN 60950:1992+A1+A2+A3+A4+A11 (electrical safety) 89/336/EEC EMC Directive: EN 50081-2: 1998 Generic Emission Standard – Industrial Environment EN 55022 based on CISPR 22, class B (Information Technology Equipment)

Narrowband

UHF bands: 403 –
470 MHz Channel
Spacing: 12.5 - 25
kHz ; RF power: 500
- 1,000mW; Transmission speed:
4.8/9.6 kbps @ 12.5 kHz, 9.6/19.2
kbps @ 25 kHz

Optional Wi-Fi Radio

IEEE 802.11a/b/g, 802.1X, WPA /
WPA2-Enterprise & Shared Key,
FAST-MSCHAPv2; PEAPv0-
MSCHAPv2; PEAPv1-GTC; TLS,
64/128 WEP, AESCCMP, TKIP

EN 50082-1: 1997 Generic

Immunity Standard – Industrial
Environment
EN 61000-4-2 ESD
EN 61000-4-3 Radiated RF
Immunity
EN 61000-4-4 Electrical Fast
Transients
EN 61000-4-5 Surge withstand

Environmental

RoHS Compliant

ANTENNA OPTIONS

Choose from indoor and outdoor UHF, 2.4 and 5GHz
omni-directional, directional and sector panel high gain
antennae.

Supports antennae for bridging (WDS) applications

Antennae diversity is supported for 802.11 radios

WARRANTY

Subject to the terms of Zebra's hardware warranty
statement, the 9160 G2 is warranted against defects in
workmanship and materials for a period of 1 (one) year
from the date of shipment. For complete warranty
statement, go to: www.zebra.com/warranty



ZEBRA

Part number: SS-9160G2. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES