



### Overview

WayPoint30A4U Outdoor Power Supply provides 24VAC and/or 28VAC distributed via four (4) fuse protected outputs for powering CCTV cameras, heaters, and other video accessories.



### Specifications

#### **Input:**

- Input: 115VAC, 50/60Hz, 3.0 amp or 230VAC, 50/60Hz, 1.5 amp.

#### **Output:**

- Output options:
  - a. 24VAC @ 12.5 amp max.
  - b. 28VAC @ 10 amp max.
- Output fuses rated @ 5A/32V.

#### **Environmental:**

- Operating Ambient Temperature:
  - 24VAC @ 12.5A output:
    - 40°C to 60°C (-40°F to 140°F);
  - 28VAC @ 10A output:
    - 40°C to 70°C (-40°F to 158°F).
- Relative Humidity: 85%, +/- 5%.
- Storage Temperature: -40°C to 75°C (-40°F to 167°F).
- Operating Altitude:
  - 304.8 to 2000m (-1000 to 6,561.679 ft.).

#### **Electrical:**

- 153.55 BTU/Hr.:
- System AC input VA requirement: 345VA.

#### **Visual Indicators:**

- Individual power output LED indicators.
- Illuminated master power switch.

#### **Mechanical:**

- NEMA 4/4X, IP66-11 Rated enclosure for outdoor use.
- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens.
- Lockable stainless steel latches.
- Integral flanges simplify wall or pole mounting.
- Enclosure Dimensions (H x W x D approx.):
  - 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm).
- Product weight (approx.): 15.45 lbs. (7.01 kg).
- Shipping weight (approx.): 16.75 lbs. (7.6 kg).

### Agency Approvals



UL/CUL Listed for Information Technology Equipment (UL 60950-1) and Equipment to be Installed Outdoors (UL 60950-22).



European Conformity

### **PMK1 Pole Mount Kit (order separately)**



PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8" (diameter) poles.
- Kit includes:
  - Two (2) powder coated steel mount brackets.
  - Four (4) stainless steel bolts.
  - Four (4) stainless steel lock washers.
  - Two (2) wormgear quick release straps.

**Enclosure Dimensions (H x W x D):**  
 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)

