



WayPoint30ADU

Overview

WayPoint30ADU Outdoor Power Supply provides 24VAC and/or 28VAC distributed via two (2) PTC protected outputs for powering CCTV Cameras, heaters, and other video accessories.



Specifications

Input:

- Input: 115VAC, 50/60Hz, 3.0 amp or 230VAC, 50/60Hz, 1.5 amp.

Output:

- Output options:
 - a. 24VAC @ 12.5 amp max.
 - b. 28VAC @ 10 amp max.
 - c. Both 24VAC and 28VAC not to exceed 10 amp max.
- Output PTCs rated @ 9A.

Environmental:

- Operating Ambient Temperature:
 - 24VAC @ 12.5A output:
 - 40°C to 60°C (-40°F to 140°F);
 - 28VAC @ 10A output:
 - 40°C to 70°C (-40°F to 158°F).
- Relative Humidity: 85%, +/- 5%.
- Storage Temperature: -40°C to 75°C (-40°F to 167°F).
- Operating Altitude:
 - 304.8 to 2000m (-1000 to 6,561.679 ft.).

Electrical:

- 153.55 BTU/Hr.:
- System AC input VA requirement: 345VA.

Visual Indicators:

- Individual power output LED indicators.
- Illuminated master power switch.

Mechanical:

- NEMA 4/4X, IP66-11 Rated enclosure for outdoor use.
- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens.
- Lockable stainless steel latches.
- Integral flanges simplify wall or pole mounting.
- Enclosure Dimensions (H x W x D approx.): 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm).
- Product weight (approx.): 15.45 lbs. (7.01 kg).
- Shipping weight (approx.): 16.75 lbs. (7.6 kg).

Agency Approvals



UL/CUL Listed for Information Technology Equipment (UL 60950-1) and Equipment to be Installed Outdoors (UL 60950-22).



European Conformity

PMK1 Pole Mount Kit (order separately)



PMK1

PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8" (diameter) poles.
- Kit includes:
 - Two (2) powder coated steel mount brackets.
 - Four (4) stainless steel bolts.
 - Four (4) stainless steel lock washers.
 - Two (2) wormgear quick release straps.

Enclosure Dimensions (H x W x D):
13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)

