

**Altronix®**

WPTV248300220 **AC Outdoor CCTV Power Supply**

Rev. DSWPTV248300220_06252015



WPTV248300220

Overview

WPTV248300220 outdoor CCTV Power Supply provides power via eight (8) fuse protected outputs for CCTV Cameras, heaters, and other video accessories.

Specifications

Input:

- 220VAC 50/60Hz, 1.4 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 12.5 amp or 28VAC @ 10 amp.
- Outputs are rated @ 3.5 amp.
- Main fuse rated @ 15 amp/32V.
- Surge suppression.

Visual Indicators:

- AC power LED.

Electrical:

- Operating temperature: -20° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 114 BTU/Hr.
 - 28VAC: 106 BTU/Hr.
- System AC input VA requirement: 308VAC.

Features:

- Illuminated master power switch with built-in circuit breaker.
- Spare fuses provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.

Mechanical:

- NEMA 4 Rated enclosure for outdoor use.
- Enclosure dimensions (H x W x D approx.): 12" x 8" x 6" (305mm x 203mm x 152mm).
- Product weight (approx.): 15.15 lbs. (6.87 kg).
- Shipping weight (approx.): 16.4 lbs. (7.44 kg).

Agency Approvals



European Conformity

PMK1 Pole Mount Kit (order separately)



PMK1

PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8"(diameter) poles.
- Kit includes:
 - Two (2) powder coated steel mount brackets.
 - Four (4) stainless steel bolts.
 - Four (4) stainless steel lock washers.
 - Two (2) wormgear quick release straps.

Enclosure Dimensions (H x W x D approximate):

12" x 8" x 6" (305mm x 203mm x 152mm)

