

AXIS Q1941-E Thermal Network Camera

Outstanding detection and powerful video analytics

AXIS Q1941-E is an affordable outdoor, bullet style, thermal camera with a built-in window heater for harsh weather conditions. A resolution of 384x288 and a range of lens alternatives (7 mm, 13 mm, 19 mm, 35 mm and 60 mm) make it possible to optimize detection performance to meet most requirements. It supports Electronic Image Stabilization that keeps the video smooth during vibrations, and Axis' Zipstream that lowers bandwidth and storage requirements. Thanks to its powerful processor, AXIS Q1941-E has high capacity for running video analytics via AXIS Camera Application Platform (ACAP) and can use a range of third party applications.

- > [High performance for intelligent video analytics via ACAP](#)
- > [Outstanding image contrast gives reliable detection and fast verification](#)
- > [Electronic Image Stabilization](#)
- > [Axis' Zipstream technology](#)



AXIS Q1941-E Thermal Network Camera

Models	AXIS Q1941-E 7 mm/13 mm/19 mm/35 mm or 60 mm	Sustainability	PVC free
Camera		Memory	512 MB RAM, 256 MB Flash
Image sensor	Uncooled Micro bolometer 384x288, pixel size: 17 µm Spectral range: 8–14 µm	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 11.8 W 8–28 V DC: typical 6.6 W, max 13 W 20–24 V AC (50/60 Hz): typical 11 VA, max 19 VA Power supply not included.
Lens	7 mm: Horizontal field of view: 55° view, F1.2 13 mm: Horizontal field of view: 28° view, F1.0 19 mm: Horizontal field of view: 19.4° view, F1.23 35 mm: Horizontal field of view: 10.7° view, F1.2 60 mm: Horizontal field of view: 6.2° view, F1.25	Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O connector for DC or AC input, two configurable inputs/outputs and mic in/line in, line out. (AXIS Multicable A I/O Audio not included) AC/DC input
Sensitivity	NETD < 70 mK	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Video		Operating conditions	–40 °C to 60 °C (–40 °F to 140 °F) Humidity 10–100% RH (condensing)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Storage conditions	–40 °C to 70 °C (–40 °F to 158 °F)
Resolutions	Sensor is 384x288. Image can be scaled up to 768x576.	Approvals	EMC EN 55022 Class A, EN 50121–4, IEC 62236–4, EN 55024, EN 61000–6–1, EN 61000–6–2, FCC Part 15 Subpart B Class A, ICES–003 Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A KCC KN22 Class A, KN24 Safety IEC/EN/UL 60950–1, IEC/EN/UL 60950–22 Environment EN 50581, IEC 60529 IP66/IP67, NEMA 250 Type 4X, IEC 60068–2–1, IEC 60068–2–2, IEC 60068–2–6 Class 4M4, IEC 60068–2–27, IEC 60068–2–52, IEC 60721–3–4 Class 4K3
Frame rate	Up to 8.3 fps and 30 fps	Dimensions	344 x 146 mm (13 9/16 x 5 3/4 in)
Video streaming	At least three H.264 and Motion JPEG streams, simultaneous and individually configured in max. resolution in full frame rate Axis' Zipstream Technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Weight	7/13/19/35 mm: 2000 g (4.4 lb) 60 mm: 2200 g (4.9 lb)
Image settings	Compression, Brightness, Sharpness, Contrast, Exposure zone, Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy mask, Mirroring of images, Electronic Image Stabilization, Multiple palettes	Included accessories	Resistorx® L-key Wall and ceiling mount bracket, AXIS Video Motion Detection 3, Terminal block connector Installation Guide, Windows decoder 1-user license
Audio		Optional accessories	AXIS T98A17-VE Surveillance Cabinet, AXIS T94G01P, AXIS T91A47 Pole Mount, AXIS Multicable A I/O Audio, Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS T8415 Wireless Installation Tool For more accessories, see www.axis.com
Audio streaming	Two-way, full duplex	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Audio input/output	External microphone input or line input, Line output	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Network		Export control	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Environmental responsibility: www.axis.com/environmental-responsibility	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	General	
System integration		Casing	IP66-, IP67- and NEMA 4X-rated Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org		
Analytics	AXIS Video Motion Detection 3, Audio detection, Shock detection Support for AXIS Camera Application Platform, see www.axis.com/acap		
Event triggers	Analytics, Temperature, External input, Time scheduled, Edge storage events		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering Play audio clip, Overlay text		
Data streaming	Event data		
Built-in installation aids	Pixel counter		

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).