

AXIS M3045-V Network Camera

HDTV 1080p fixed mini dome with HDMI

AXIS M3045-V is an affordably priced, vandal- and dust-resistant indoor fixed dome. The camera has an integrated RJ45 Ethernet connection and supports Power over Ethernet (PoE). WDR ensures that details in both the dark and bright areas of a scene are visible. HDMI support enables live streaming to an HDTV monitor for e.g. public viewing. The factory-focused camera can be mounted on walls or ceilings and with its 3-axis camera angle adjustment it can be easily leveled and directed in any direction. Axis' Corridor Format enables vertically oriented video streams. AXIS M3045-V supports video analytics such as people counting.

- > **Ultra-compact, vandal- and dust-resistant design**
- > **HDTV 1080p / 2 MP**
- > **HDMI support enables streaming to a monitor**
- > **Axis' Zipstream technology for reduced bandwidth and storage**
- > **Axis' Corridor Format**



AXIS M3045-V Network Camera

Camera		Overlay text	
Image sensor	1/3" progressive scan RGB CMOS	Data streaming	Event data
Lens	M12 mount, Fixed iris, Fixed focus 2.8 mm, F2.0 Horizontal field of view: 106° Vertical field of view: 59°	Built-in installation aids	Pixel counter
Light sensitivity	0.25 lux at 50 IRE F2.0	General	
Shutter time	1/32500 s to 1/5 s	Casing	Color: White NCS S 1002-B (For repainting of cover, remove the transparent dome. Contact your Axis partner for repainting instructions), Encapsulated electronics, Captive screws (Torx 10) IP42 water- and dust-resistant (to comply with IP42, follow instructions in Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing
Camera angle adjustment	Pan ±177°, Tilt ±69°, Rotation ±176° Can be directed in any direction and see the wall/ceiling	Sustainability	PVC free
Video		Memory	512 MB RAM, 256 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profiles, Motion JPEG	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.6 W, max 3.0 W
Resolutions	1920x1080 (1080p) to 320x240 HDMI 1080p@25/30 fps (50/60 Hz) HDMI 1080i@50/60 fps (50/60 Hz) HDMI 720p@50/60 fps (50/60 Hz) HDMI 720p@25/30 fps (50/60 Hz)	Connectors	RJ45 10BASE-T/100BASE-TX PoE HDMI Type D
Frame rate	25/30 fps with power line frequency 50/60 Hz	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For memory card and NAS recommendations see www.axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, Axis' Zipstream technology in H.264, VBR/MBR H.264 HDMI	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 15-85% RH (non-condensing)
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F) Humidity 15-85% RH (non-condensing)
Pan/Tilt/Zoom	Digital PTZ	Approvals	EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35, IEC/EN/UL 60950-1, IEC/EN 60529 IP42, IEC/EN 62262 Class IK08
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Backlight compensation, WDR, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Dimensions	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
Network		Weight	170 g (0.38 lb)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Included accessories	Installation Guide, Windows decoder 1-user license, Torx L-key
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI 1.4b	Optional accessories	AXIS T94 mounts for various installations Black casing Smoked dome Cover view AXIS Surveillance microSDXC [™] Card 64 GB
System integration		Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Event triggers	Analytics, Edge storage events	<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p> <p>Environmental responsibility: www.axis.com/environmental-responsibility</p>	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering		