

Switch Accessories

SFP

		
1 GbE SFP Copper Module For: All MS series switches Standard: 1000BASE-T Range: 100m	1 GbE SFP SX Fiber Transceiver For: All MS series switches Standard: 1000BASE-SX Range: 550m	1 GbE SFP LX Fiber Transceiver For: All MS series switches Standard: 1000BASE-LX10 Range: 10km

SFP+

		
10 GbE SFP+ SR Fiber Transceiver For: MS225, MS250, MS350, MS410, and MS425 Standard: 10GBASE-SR Range: 400m	10 GbE SFP+ LR Fiber Transceiver For: MS225, MS250, MS350, MS410, and MS425 Standard: 10GBASE-LR Range: 10km	10 GbE SFP+ LRM Fiber Transceiver For: MS225, MS250, MS350, MS410, and MS425 Standard: 10GBASE-LRM Range: 220m

QSFP+

		
40 GbE QSFP+ SR4 Fiber Transceiver For: MS425 Standard: 40GBASE-SR4 Range: 150m	40 GbE QSFP+ LR4 Fiber Transceiver For: MS425 Standard: 40GBASE-LR4 Range: 10km	40 GbE QSFP+ CSR4 Fiber Transceiver For: MS425 Standard: 40GBASE-CSR4 Range: 400m



40 GbE QSFP+ SR-BD Fiber Transceiver

For: MS425
Standard: 40GBASE-SR-BD
Range: 150m

Twinax



Twinax Cable with SFP+ Connectors (1m)

For: MS225, MS250, MS350, MS410, and MS425
Standard: SFP+ Direct Attach (10GSFP+Cu)
Range: 1m



Twinax Cable with SFP+ Connectors (3m)

For: MS225, MS250, MS350, MS410, and MS425
Standard: SFP+ Direct Attach (10GSFP+Cu)
Range: 3m

Stacking



Stacking Cable (0.5m)

For: MS225, MS250, MS350, MS410 and MS425
Range: 0.5m



Stacking Cable (1m)

For: MS225, MS250, MS350, MS410 and MS425
Range: 1m



Stacking Cable (3m)

For: MS225, MS250, MS350, MS410 and MS425
Range: 3m

Fans



16K RPM Fan

For: MS350 and MS410



18K RPM Fan

For: MS425 and MS350-24X

Mounting



Mounting Brackets

For: MS225 and MS250

Power



250 Watt Power Supply

For: MS250, MS350, MS410 and MS425
Power: 250 W



640 Watt Power Supply

For: MS250 P/LP and MS350 P/LP
Power: 640 W



1025 Watt Power Supply

For: MS250 FP, MS350 FP and MS350-24X
Power: 1025 W



Power cord (US, EU, UK or AU)

For: All MS series switches

[Download SFP datasheet](#)

Module 'pgsql' already loaded Unknown :0